

NEED HELP SELECTING AN HVAC PUMP?

There's a reason we've been the go-to pump for HVAC, Plumbing, Pool, and Hydroponics professionals for generations: experience. For over 80 years, Little Giant products have stood the test of time, pumping a steady flow of proven reliability in the most demanding applications.

LittleGIANT®

Get started with our selection tool and featured solutions for HVAC applications.

littlegiant.com



1 What type of job do you have?

	UTILITY	CONDENSATE REMOVAL	LOW PROFILE	PLENUM & HIGH TEMPERATURE	MINI-SPLIT	IN-PAN	SPECIALTY
Common Equipment & Installation Examples	Emergency dewatering in basements and crawlspaces; draining hot water tanks	Air conditioners, condensing furnaces, boilers, and dehumidifiers	Air conditioners and condensing furnaces with limited space for pump installation	Above-ceiling and below-floor Plenum applications; condensing boiler equipment	Wall mounts and ductless, mini-split air conditioners (up to 34,000 Btu)	Air conditioners and refrigeration equipment where in-pan condensate removal is the only option	Evaporative cooler pump replacement and commercial ice machine equipment
Shut-Off Ranges	25 ft to 145 ft	15 ft to 45 ft	20 ft	32 ft to 62 ft	33 ft	10 ft	9.5 ft to 12 ft
Flow-Rate Ranges	20 gpm to 80 gpm	60 gph to 450 gph	80 gph	350 gph to 575 gph	2.7 gph	205 gph	307 gph to 563 gph

2 A few other job requirements to consider:

Collection Tank Size	n/a	1/2 gallon to 1 gallon	3/10 gallon	1 gallon	n/a	n/a	n/a
Max Water Temperature	140 °F (60 °C)	120 °F (49 °C) to 140 °F (60 °C)	120 °F (49 °C) to 140 °F (60 °C)	212 °F (100 °C)	140 °F (60 °C)	120 °F (49 °C)	120 °F (49 °C)
Housing/Tank Cover Material	Stainless Steel, Plated Brass, Cast Iron, Cast Aluminum	ABS	ABS	Polymer	Polymer	Epoxy-Coated Cast Aluminum	ABS, Polystyrene
Tank/Impeller Material	Polypropylene, Stainless Steel	Polypropylene, ABS	ABS, Glass-Filled Polypropylene	Polypropylene	n/a	Nylon	ABS, Polystyrene
Horsepower Ranges	1/6 hp to 1 hp	1/50 hp to 1/5 hp	1/30 hp	1/8 hp to 1/3 hp	n/a	1/150 hp	1/70 hp to 1/25 hp
Discharge/Check Valve	3/4" to 2"	3/8"	1/4" to 3/8"	3/8"	1/4"	1/4" NPT	Various
Input Voltage	115V or 230V	115V or 230V	115V or 230V	115V, 208-230V, 277V, 380-460V	110-240V	115V or 230V	115/127V, 230V
Safety Overflow Switch	n/a	✓	✓	✓	✓	✗	n/a
Standard Warranty							

3 Here are some solutions; utility or HVAC pumps, we have you covered!

Featured Series <i>Learn more at littlegiant.com or contact your sales representative for additional options.</i>	5 Series	Pony Pump	VCMA Series	VCMA-Pro Series	VCCA-20ULS	HT-VCL-30-P	EC-1-DV	1-ABS	CP Series
	FLS/FS Series	UPSP	VCL Series		VCCA-20-P	HT-VCL-60-P	EC-1K-DV		RIM-U